



Concrete cylinder finisher CF1250H

[Orders](#)

[Hotline](#)

[Chat zalo](#)

[Whatsapp](#)

[Facebook](#)

The Concrete Cylinder Finisher CF1250 - Hydraulic is a perfect chosen for for concrete road paving as well as floors construction, Bridges surface, Airports, Sloop paving etc.

TECHNICAL SPECIFICATIONS

- Productivity : 150 square meter/ hour with single drum; 300 square meter/ hour with double drum.
 - Paving width standard 2,5m – 6m. Can be paving up to 20m width with adding frame.
 - modular frame made from welded steel panels, quickly install, be sure strong enough and easy transportation.
 - finishing width is infinitely adjustable to within 1,25 meter less than the overall width. Finishing width adjustment are made from the operators control panel using automatic reverse controls
 - four grade jacks, manually height adjustable
 - four pairs of double flange wheels, 80 mm wide, by 140 mm diameter. Two pairs are hydraulically driven and two pairs are idle
 - 250 mm diameter augers, for finishing carriage. One left hand, one right hand, with guard
 - finishing cylinder mounted on finishing carriage, 250 mm diameter by 1250 mm long
 - double chain undercarriage drive
 - double rail/double wheel undercarriage guide
 - designed for operation on flat and inclined surfaces without modification to basic frame structure.
-





Related Products



—

[Concrete cylinder finisher CF1250E](#)