



Cigarettes

Silicon is used to store bulk materials (cement, fly ash, stone powder ...) with a capacity of 60 tons to 200 tons.

[Orders](#)

[Hotline](#)

[Chat zalo](#)

[Whatsapp](#)

[Facebook](#)

- The body of the silo is whirled and tapered on a dedicated cyclone to ensure a consistent and uniform round.
- Welds are welded on MIG - MAG welding machines with a team of skilled workers, ensuring the tight seal, durable.
- Silicon paint process ensures quality standard TCVN334-2005, paint 3 layers (1 anti-rust layer + 2 paint) with a total paint thickness of 90µm. Check the thickness of paint by specialized equipment imported from Europe.
- System: dust filter designed to ensure effective dust, friendly people and surrounding environment.

	SL-60	SL-80	SL-100	SL-120	SL-150	SL-200
Storage capacity (m3 / ton)	46/60	62/80	83/100	90/120	113/150	145/200
Diameter of silicon D (mm)	2660	2830	3400	3400	3400	4700
Overall height H1 (mm)	12873	14400	14876	15586	22000	16389
Heel height H24000 (mm)		4000	4200	4200	4200	6594
Height of outlet mouth H3 (mm)	2331	2250	2300	2300	2300	3534
Material	Ct3	Ct3	Ct3	Ct3	Ct3	Ct3



Contact 0916 427 068 - 0902 686 002 - Mr.Dũng for advice and receive the best quotation.

Related Products

Currently there are no news items.